

Revision date: 15/03/2017

# CREOSEAL LTD

## SAFETY DATA SHEET

### RED OXIDE METAL PRIMER

#### **SECTION 1: Identification of the substance/mixture and of the company/ undertaking**

##### **Product identifier**

Product Name:Red Oxide Metal Primer

##### **Relevant identified uses of the substance or mixture and uses advised against**

Product use:Solvent borne coating for interior and exterior use

##### **Details of the supplier of the safety data sheet**

Creoseal Ltd  
7-9 Brook Street  
Sileby  
Loughborough  
Leicestershire  
LE12 7RF  
01509 812473

Email address and person responsible for this SDS: enquiries@creoseal.co.uk

##### **Emergency telephone number**

##### **Supplier**

Telephone number: 01509 812473

##### **National Advisory body/Poison Centre**

Telephone number: +44 844 892 0111 / 112

#### **SECTION 2: Hazards identification:**

##### **2.1 Classification of the substance or mixture**

Product definition:Mixture

**Classification according to regulation (EC) No, 1272/2008 [CLP/GHS]**

Flam. Liq. 3, H226

STOT SE 3, H336

Aquatic Chronic 3, H412

**Ingredients of known toxicity:**0%

**Ingredients of unknown toxicity:**0%

See section 16 for the full text of the H statements declared above.

See section 11 for more detailed information on health effects and symptoms.

**2.2 Label elements**

**Hazard pictograms:**

**Signal word:**Warning

**Hazard statements:**H226 – Flammable liquid and vapour.

H336 – May cause drowsiness or dizziness.

H411 – Toxic to aquatic life with long lasting effects.

**Precautionary statements:**

**General:**P102 Keep out of reach of children

P101 If medical advice is needed, have product container or label to hand.

**Prevention:**P210 – Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 – Avoid breathing vapour or spray

P273 – Avoid release into the environment

P303, P362, P353 – IF ON SKIN (or hair) take off immediately all contaminated clothing. Rinse skin with water or shower.

P262 – Do not get in eyes, on skin, or on clothing.

**Response:**P304 + P340 – IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 – Call a POISON CENTRE or doctor if you feel unwell.

**Storage:**P403, P233 – Store in a well ventilated place. Keep container tightly closed.

P405 -Store locked up

**Disposal:**P501 – Dispose of contents and container in accordance with all local, regional, national or international regulations.

**Hazardous ingredients:**Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics.

**Annex XVII – Restrictions on the Not Applicable manufacture, placing on the market and use of certain dangerous substances, mixtures and articles:**

**Special packaging requirements:**  
**Containers to be fitted with child Not applicable. resistant fastenings:**

**Tactile warning of danger:**Not applicable.

### 2.3 Other hazards

**Other hazards which do not result in classification:** None known.

## **SECTION 3: Composition/information on ingredients**

### **3.2 Mixtures:**Mixture

|  |  |
|--|--|
| <b>PRODUCT/INGREDIENT NAME:</b>  |  |
| Naphtha (petroleum), hydrotreated heavy – D40 Dearomatised<br>10-30%                                     |  |
| CAS-No: 64742-48-9   | EC No: 265-150-3                                     |
| Classification (EC 1272/2008)<br>Flam. Liq. 3 – H226<br>EUH066<br>STOT SE 3 - H336<br>Asp. Tox. 1 - H304 | Classification (67/548/EEC)<br>Xn;R65<br>R1-.R66,R67 |
| Naphtha (petroleum), hydrotreated heavy - D60 High Flash<br>< 1%   |  |
| CAS-No: 65742-48-9   |  |
| Classification (EC 1272/2008)<br>EUH066<br>STOT SE 3 – H336<br>Asp. Tox. 1 - H304                        | Classification (67/548EEC)<br>Xn;R65<br>R66,R67      |

|                               |                             |
|-------------------------------|-----------------------------|
| XYLENE<br>< 1%                |                             |
| CAS NO:1330-20-7              | EC No:215-535-7             |
| Classification (EC 1272/2008) | Classification (67/548/EEC) |
| Flam. Liq. 3 - H226           | R10                         |
| Acute Tox. 4 - H312           | Xn;R20/21                   |
| Acute Tox. 4 - H332           | Xn;R38                      |
| Skin Irrit. 2 - H315          |                             |
|                               |                             |
|                               |                             |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No, 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No, 1907/2006, Annex XIII
- [5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

### **Section 4: First aid measures:**

#### **4.1 Description of first aid measures**

**General:**In all cases of doubt, or when symptoms persist, seek medical attention, Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.

**Eye Contact:**Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

**Inhalation:**Remove to fresh air. Keep person warm and at rest. If no breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

**Skin contact:**Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

**Ingestion:**If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.

**Protection of first-aiders:**No action shall be taken involving any personal risk or without

suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-mouth resuscitation.

#### **4.2 Most important symptoms and effects, both acute and delayed**

There are no data available on the mixture itself. The mixture has been assessed following the conventional methods of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse effects on the kidneys, liver and the central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in, extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 2-butanone oxime. May produce an allergic reaction.

#### **4.3 Indication of any immediate medical attention and special treatment needed**

**Notes to physician:** Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

**Specific Treatments:** No specific treatment

See toxicological information (Section 11)

### **Section 5: Firefighting measures:**

#### **5.1 Extinguishing media**

**Suitable extinguishing** Recommended: alcohol-resistant foam, CO<sub>2</sub> powders, water spray.

**media:**

**Unsuitable extinguishing** Do not use water jet.

**media:**

|  |  |
|--|--|
| <b>Hazards from the substance or mixture:</b>    | Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.                     |
| <b>Hazardous thermal decomposition products:</b> | Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen |

## 5.2 Special hazards arising from the substance or mixture

### 5.3 Advise for firefighters

|   |   |
|---|---|
| <b>Special protective actions for firefighters:</b>   | Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses. |
| <b>Special protective equipment for firefighters:</b> | Appropriate breathing apparatus may be required.  |

## **Section 6: Accidental release measures:**

### **6.1 Personal precautions, protective equipment and emergency procedures**

|  |   |
|--|---|
| <b>For non-emergency personnel</b>                               | Exclude source of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.   |
| <b>For emergency responders:</b>                                 | If specialized clothing is required to deal with the spillage take note of any information in Section 8 on suitable and unsuitable materials, See also the information in 'For non-emergency personnel'.  |
| <b>6.2 Environmental precautions:</b>                            | Do not allow to enter drains or watercourses. If the product contaminated lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.  |
| <b>6.3 Methods and material for containment and cleaning up:</b> | Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents. |

|   |  |
|---|--|
| <p><b>6.4 Reference to other sections</b></p> | <p>See Section 1 for emergency contact information.<br/>See Section 8 for information on appropriate personal protective equipment.<br/>See Section 13 for additional waste treatment information.</p> |
|---|--|

**Section 7: Handling and storage:**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

**7.1 Precautions for safe handling** Prevent the creation of flammable or explosive concentrations of vapour in the air and avoid vapour concentrations higher than the occupational exposure limits.

In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected in the appropriate standard.

Mixture may charge electrostatically: always use earthing leads when transferring from one container to another.

Operators should wear antistatic footwear and clothing and floors should be of the conducting type.

Keep away from heat, sparks and flame. No sparking tools should be used.

Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture.  
Avoid inhalation of dust from sanding.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.

Put on appropriate personal protective equipment (see Section 8).

Never use pressure to empty. Container is not a pressure vessel.

Always keep in containers made from the same material as the original one.

Do not allow to enter drains or watercourses.

**Information on fire and explosion protection**

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

**7.2 Conditions for safe storage, including any incompatibilities**

Store in accordance with local regulations.

**Notes on joint storage**

Keep away from: oxidizing agents, strong alkalis, strong acids.

### **Additional information on storage conditions**

Observe label precautions. Store in a dry, cool and well ventilated area. Keep away from heat and direct sunlight. Keep away from source of ignition. No smoking. Prevent unauthorized access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

### **Seveso Directive – Reporting thresholds (in tonnes)**

#### **Danger Criteria:**

| <b>Category:</b>  | <b>Notification and MAPP threshold:</b> | <b>Safety report threshold:</b> |
|---|---|---------------------------------|
| P5c: Flammable liquids 2 and 3 not falling under P5a or P5b | 5000                                    | 50 000                          |
| C6: Flammable (R10)   | 5000                                    | 50 000                          |

### **7.3 Specific end use(s)**

**Recommendations:**Not available.

**Industrial sector specific solutions:**Not available.

### **Section 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

#### **8.1 Control parameters**

##### **Occupational exposure limits**

No exposure limit value known.

##### **Recommended monitoring procedures:**

If this product contains ingredients exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmosphere – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents). European Standard EN482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

##### **DNELs/DEMLs**

No DNELs/DMELs available.



## PNECs

No PNECs available.

## **8.2 Exposure controls**

**Appropriate engineering controls:** Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn.

### **Individual protection measures:**

**Hygiene measures:** Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection:** Use safety eyewear designed to protect against splash of liquids.

### **Skin protection:**

#### **Hand protection:**

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical, chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

**Body Protection:** Personnel should wear antistatic clothing made of natural fibers or of high-temperature-resistant synthetic fibers.

**Other skin protection:** Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling

the product.

**Respiratory protection** If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators.

#### OLD LEAD-BASED PAINTS:

When surfaces are to be prepared for painting, account should be taken of the age of the property and the possibility that lead-pigmented paint might be present. There is a possibility that ingestion or inhalation of scrapings or dust arising from the preparation work could cause health effects. As a working rule you should assume that this will be the case if the age of the property is pre 1960.

Where possible wet sanding or chemical stripping methods should be used with surfaces of this type to avoid the creation of dust. When dry sanding cannot be avoided, and effective local exhaust ventilation is not available it is recommended that a dust respirator is worn, that is approved for use with lead dusts, and its type selected on the basis of the COSHH assessment, taking into account the Workplace Exposure Limit for lead in air. Furthermore, steps should be taken to ensure containment of the dusts created, and that all practicable measures are taken to clean up thoroughly all deposits of dusts in and around the affected area.

Respiratory protection in case of dust or spray mist formation (particle filter EN143 type P2). Respiratory protection in case of vapour formation (half mask with combination filter A2-P2 til concentrations of 0.5Vol%).

The current Control of Lead at Work Regulations approved code of practice should be consulted for advice on protective clothing and personal hygiene precautions. Care should also be taken to exclude visitors, members of the household and especially children from the affected area, during the actual work and the subsequent clean up operations. All scrapings, dust, etc. should be disposed of by the professional painting

contractor as Hazardous Waste.

Extra precautions will also need to be taken when burning off old lead-based paints because fumes containing lead will be produced. It is recommended that a respirator, approved for use with particulate fumes of lead is selected on the basis of the COSHH assessment, taking into account the Workplace Exposure Limit for lead in air. Similar precautions to those given above about sanding should be taken with reference to protective clothing, disposal of scrapings and dusts, and exclusion of other personnel and especially children from the building during actual work and the subsequent clean up operations.

Page 9

Avoid inhalation of dust. Wear suitable face mask if dry sanding. Special precautions should be taken during surface preparations of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

**Environmental exposure controls:** Do not allow to enter drains or watercourses.

## **Section 9: Physical and chemical properties:**

### **9.1 Information on basic physical and chemical properties**

#### **Appearance:**

**Physical State:** Liquid

**Colour:** Not available.

**Odour:** Not available.

**Odour threshold:** Not available.

**pH:** Not available.

**Melting point/freezing point:** Not available.

**Initial boiling point and boiling range:** 149<sup>o</sup>C

**Flash point:** Closed cup: 32<sup>o</sup>C

**Evaporation rate:** Not available.

**Upper/lower flammability or explosive limits:** Not available.

**Vapour pressure:** Not available.

**Vapour density:** Not available.

**Relative density:** 1.275

**Solubility(ies):** Insoluble in the following materials: cold water.

**Solubility in water:** Not available.

**Partition coefficient: n-octanol/water:** Not available.

**Auto-ignition temperature:** Not available.

**Decomposition temperature:**Not available.

**Viscosity:Kinematic (room temperature):** 5.5cm<sup>2</sup>/s

**Explosive properties:**Not available.

**Oxidising properties:**Not available.

## **9.2 Other information**

There is no additional information.

## **Section 10: Stability and reactivity:**

**10.1 Reactivity:**No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability:**Stable under recommended storage and handling conditions (see Section 7).

**10.3 Possibility of hazardous reactions:**Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid:**When exposed to high temperatures may produce hazardous decomposition products.

**10.5 Incompatible materials:**Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

**10.6 Hazardous decomposition products:**Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## **Section 11: Toxicological Information:**

### **11.1 Information on toxicological effects**

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse effects such as mucous membrane and respiratory system irritation and adverse effects on the weakness, drowsiness and in extreme cases loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed into the eyes, the liquid may cause irritation and reversible damage.

Ingestion ay cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic

effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 2-butanone oxime. May produce an allergic reaction.

**Acute toxicity:**

**Conclusions/summary:**Not available.

**Acute toxicity estimates:**

Not available.

**Irritation/Corrosion:**

| <b>Product/<br/>ingredient<br/>name</b> | <b>Result</b>          | <b>Species</b> | <b>Score</b> | <b>Exposure</b> | <b>Observation</b> |
|---|------------------------|----------------|--------------|-----------------|--------------------|
| 2-butanone oxime                        | Eyes – Severe irritant | Rabbit         | -            | -               | -                  |

**Conclusion/Summary:**Not available.

**Sensitisation:**

**Conclusion/Summary:**Not available.

**Mutagenicity:**

**Conclusion/Summary:**Not available.

**Carcinogenicity:**

**Conclusion/Summary:**Not available.

**Reproductive toxicity:**

**Conclusion/Summary:**Not available.

**Teratogenicity:**

**Conclusion/Summary:**Not available.

**Specific target organ toxicity (single exposure):**

| <b>Product/<br/>ingredient name:</b>                                | <b>Category:</b> | <b>Route of exposure:</b> | <b>Target organs:</b> |
|---|------------------|---------------------------|-----------------------|
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | Category 3       | Not applicable.           | Narcotic effects      |

**Specific target organs toxicity (repeated exposure):**

Not available.

**Aspiration hazard:**

| <b>Product/ingredient name:</b>                                      | <b>Result:</b>                 |
|--|--------------------------------|
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics  | ASPIRATION HAZARD – Category 1 |
| Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics | ASPIRATION HAZARD – Category 1 |

**Other information:**Not available.

**Section 12: Ecological information:**

**12.1 Toxicity**

There are no data available on the mixture itself.

Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See sections 2 and 3 for details.

**Conclusions/summary:**Not available.

**12.3 Bioaccumulative potential**

**12.4 Mobility in soil**

**Soil/water partition coefficient ( $K_{oc}$ ):**Not available.

**Mobility:**Not available.

**12.5 Results of PBT and vPvB assessment**

**PBT:**Not applicable.

P: Not available. B: Not available. T: Not available.

**vPvB:**Not applicable.

vP: Not available. vB: Not available.

**12.6 Other adverse effects:**No known significant effects or critical hazards.

**Section 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of

Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### **13.1 Waste treatment methods:**

#### **Product:**

**Methods of disposal:**The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste:**The classification of the product may meet the criteria for a hazardous waste.

**Disposal considerations:**Do not allow to enter drains or watercourses.

Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

#### **Packaging:**

**Methods of disposal:**The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Disposal considerations:**Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers.

Empty containers must be scrapped or reconditioned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions.

**Special precautions:**The material and its container must be disposed of in a safe way.

Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or lines may retain some product residues. Vapour from product residues may create a

highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

**Section 14: Transport information:**

**INFORMTAION PERTAINING TO IATA AND AND IS CONSIDERED NOT RELEVANT SINCE THE MATERIAL IS NOT PACKAHD IN THE CORRECT APPROVED PACKAGING REQUIRED OF THESE METHODS OF TRANSPORT.**

|   | <b>ADR</b>   | <b>IMDG</b>          |
|---|--|----------------------|
| <b>14.1 UN Number</b>   | <b>UN1263</b>  | <b>UN1263</b>        |
| <b>14.2 UN Proper Shipping Name</b>   | <b>Paint</b>   | <b>Paint</b>         |
| <b>14.3 Transport hazard class(es)</b>  |  |                      |
| <b>Class</b>  | <b>3</b>   | <b>3</b>             |
| <b>Subsidiary class</b>   | <b>-</b>   | <b>-</b>             |
| <b>14.4 Packing group</b>   | <b>III</b>   | <b>III</b>           |
| <b>14.5 Environmental hazards</b>   |  |                      |
| <b>Marine pollutant</b>   | <b>No</b>  | <b>No</b>            |
| <b>Marine pollutant substances</b>  |  | <b>Not available</b> |
| <b>14.6 Special precautions for user</b>  | <b>Transport within user's premises:</b><br>Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage. |                      |
| <b>HI/Kremler number</b>  |  |                      |
| <b>Emergency Schedules (EmS)</b>  | <b>30</b>  | <b>F-E, S-E</b>      |
| <b>14.7 Transport in bulk according to Annex II of MARPOL and the IBC code:</b> Not applicable. |  |                      |



|                               |   |  |
|-------------------------------|---|--|
| <b>Additional information</b> | <p><b><u>Special Provisions</u></b><br/>640 (E)</p> <p><b><u>Viscous substance exemption</u></b><br/>In pack sizes less than 450 litres, under the terms of 2.2.3.1.5, this product is not subject to provisions of ADR.</p> <p><b><u>Tunnel code</u></b><br/>(D/E)</p> | <p><b><u>Viscous substance exemption</u></b><br/>In pack sizes up to and including 30 litres, under the terms of 2.3.2.5, this product is not subject to the packaging, labelling and marking requirements of the IMDG Code, but both full documentation and placarding of cargo transport units still required.</p> |
|-------------------------------|---|--|

**Regulatory Information:**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU Regulation (EC) No. 1907/2006 (REACH)**

**Annex XIV – List of substances subject to authorization**

**Annex XIV:**

None of the components are listed.

**Substances of very high concern:**

None of the components are listed, or the component present is below its threshold.

**Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles:**  
Not available

**Other EU regulations:**

**VOC:**Not available.

**Europe inventory:**At least one component is not listed.

**Priority list chemicals:**Listed.

| <b>Product/<br/>ingredient<br/>name</b> | <b>Carcinogenic<br/>effects</b> | <b>Mutagenic<br/>effects</b> | <b>Developmental<br/>effects</b> | <b>Fertility<br/>effects</b> |
|---|---------------------------------|------------------------------|----------------------------------|------------------------------|
| 2-butanone oxime                        | Carc. 2, H351                   | -                            | -                                | -                            |

**Seveso Directive:**

This product is controlled under the Seveso Directive.

**Danger criteria:**

|                 |
|-----------------|
| <b>Category</b> |
|-----------------|

P5c: Flammable liquids 2 and 3 not falling under P5a or P5b  
C6: Flammable (R10)

**International regulations:**

**Chemical Weapon Convention List Schedules I, II, III Chemicals**

Not listed.

**Montreal Protocol (Annexes A, B, C, E)**

Not listed.

**Stockholm Convention on Persistent Organic Pollutants**

Not listed.

**Rotterdam Convention on Prior Inform Consent (PIC)**

Not listed.

**UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

**15.2 Chemical Safety assessment:**Not applicable.

**Section 16: Other information:**

**CEPE Code:**1

**Abbreviations and acronyms:**ATE= Acute Toxicity Estimate

CLP= Classification, Labelling and  
Packaging Regulation

[Regulation (EC) No. 1272/2008]

DMEL= Derived Minimal Effect Level

DNEL= Derived No Effect Level

EUH Statement= CLP=specific Hazard  
statement

PBT= Persistent, Bioaccumulative and  
Toxic

PNEC = Predicted No Effect Concentration

RPN= REACH Registration Number

vPvB= Very Persistent and Very  
Bioaccumulative

**Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]:**

| <b>Classification</b>   | <b>Justification</b>  |
|-------------------------|-----------------------|
| Flam. Liq. 3, H226      | On basis of test data |
| STOT SE 3, H336         | Calculation method    |
| Aquatic Chronic 3, H412 | Calculation method    |

**Full text of abbreviated H statements:**

|      |  |
|------|--|
| H226 | Flammable liquid and vapour                  |
| H304 | May be fatal if swallowed and enters airways |

|      |   |
|------|---|
| H312 | Harmful in contact with skin                      |
| H317 | May cause an allergic skin reaction               |
| H318 | Causes serious eye damage                         |
| H336 | May cause drowsiness or dizziness                 |
| H351 | Suspected of causing cancer                       |
| H400 | Very toxic to aquatic life                        |
| H410 | Very toxic to aquatic life with long last effects |
| H412 | Harmful to aquatic life with long lasting effects |

### Full text of classifications

|                         |  |
|-------------------------|--|
| Acute Tox. 4, H312      | CVUTE TOXICITY (dermal) – Category 4   |
| Aquatic Acute 1, H400   | ACUTE AQUATIC HAZARD – Category 1  |
| Aquatic Chronic 1, H410 | LONG-TERM AQUATIC HAZARD – Category 1  |
| Aquatic Chronic 3, H412 | LONG-TERM AQUATIC HAZARD – Category 3  |
| Asp. Tox. 1, H304       | ASPIRATION HAZARD – Category 1   |
| Carc. 2, H351           | CARCINOGENICITY – Category 2   |
| EUH066                  | Repeated exposure may cause skin dryness of cracking                             |
| Eye Dam. 1, H318        | SERIOUS EYE DAMAGE/EYE IRRITATION – Category 1                                   |
| Flam. Liq. 3, H226      | FALMMABLE LIQUIDS – Category 3   |
| Skin Sens. 1, H317      | SKIN SENSITIZATION – Category 1  |
| STOT SE 3, H336         | SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) – Category 3 |

**Date of printing:15/03/2017**

**Date of issue/Date of revision:15/03/2017**

**Date of previous issue:15/03/2017**

**Version:2**

**Notice to reader:**

***IMPORTANT NOTE:***

*The information in this data sheet, or advice given regarding the use of this product is based on the present state of our knowledge on current laws and does not therefore guarantee certain properties. Recipients of our product must not use the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as the suitability of the product for the intended purpose does so at his own risk. Always read the Material Data Sheet and the Technical Data Sheet for this product if*

*available. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any damage or loss arising out the use of the product. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product and to observe existing laws and regulation*