

7-11 Brook Street, Sileby, Loughborough, Leicestershire, LE12 7RF T: 01509 812473 E: sales@creoseal.co.uk

Safety Data Sheet

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product Identifier

Product Name: Creoseal Plus
Product Description: Wood Treatment

Products Type: Liquid

1.2 Relevant Identified Uses of the substance or mixture and uses advised against

For use as an outdoor wood preservative on external timbers, advised against any other use then those identified.

1.3 Details of the Supplier of the Safety Data Sheet

Creoseal Limited 7 – 11 Brook Street Sileby Loughborough Leicester LE12 7RF 01509 812473

1.4 Emergency telephone number

Contact NHS Direct; phone 0845 4647 or 111. Open 24/7.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition: Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

STOT RE 1, H373 Aquatic Chronic 3, H411

2.2 Label element

Hazard pictograms:



Signal word: Danger

Hazard statements:: H373 - Causes damage to organs through prolonged or repeated exposure

H411 - Harmful to aquatic life with long lasting effects.

H332 Harmful if inhaled.

Precautionary statements: H226 Flammmable Liquid and vapour

General Prevention: P273 - Avoid release to the environment.

P260 - Do not breathe vapour.

P270 - Do not eat, drink or smoke when using this product.

Response

P314 – get medical attention if you feel unwell

Storage P501 Dispose of contents in accordance with local regional, national

Disposal; and international regulations.

P403 Store in a well vanterled place.

Supplement label elements Not a

Not applicable

Hazardous ingredients hydrocarbons, C10-C13, n-alkanes, isoalkanes cyclics, aromatics

(2-25%), (.0.1% Benzene

2.3 Other Hazardous

Other hazardous which do not results in classification; None known Precautionary statements

SECTION 3; Composition/information on ingredients.

П

Product/ingredient	Identifiers	%	Regulation (EC) No.	Type	Notes
Name			1272/2008		
Hydrocarbon, C10C13,n-alkanes, isoalkanes, cyclics aromatics (2-25%, (<0.1% Benzene	Reach# 01-2119473977-17 EC; 919-164-8	>5- >20	STOT RE1, H372 Asp Tox 1, H304 Aquatic Chronic 3, H412 EU066 See section 16 for full text of the H statements declared above	(1)	H-P.4
Kerosine	(CAS) 64742-81-01 (EC No) 265-184-9	>5 - <50	Flam Liq3, H226 Skin irrit2, H315 STOT SE 3, H336 Asp Tox 1.H304 Aquatic chromic 2. H411		
Asphalt	(CAS) 64742-81-01 (EC No) 265-184-9	>5 – <30	CAS-No 8025-42-4		

There are no additional ingredients present which, within the currant knowledge of the supplier and in the concentrations applicable are classified as hazardous to health or the environmental, are PBTs prvPvPBsor or have been assigned a workplace exposure limit and hence require reporting in this section.

- (1) Substance classified with health or environmental hazard
- (2) Substance with a workplace exposure limit
- (3) Substance meets the criteria for PTB according to Regulation (EC) No. 1907/2006, Annex XIII
- (4) Substance meets the criteria for vPvB according to regulation (EC) No. 1907/2006, Annex XIII
- (5) Substance of equivalent concern

Occupational exposure limits, if available, are listed in section 8.

SECTION 4; Frist aid measures

4.1 Description of first aid measures

General

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.

Inhalation

Remove to fresh air. Keep person warm and at rest, if not breathing or irregular breathing or respiratory arrest occurs, provide artificial respiration or oxygen by trained personal.

Skin Contact

Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recongnised skin cleanser. DO NOT use solvents or thinners

Eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.

SECTION 4: First aid measures

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, dirrhoea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Potential acute health effects

Inhalation:No known significant effects or critical hazards.Ingestion:No known significant effects or critical hazards.Skin contact:No known significant effects or critical hazards.Eye contact:No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact: No specific data. Inhalation:
No specific data. Skin contact: No specific data.

Ingestion: No specific data.

Indication of any immediate medical attention and special treatment needed

Notes to physician Treat symptomatically. Contact poison treatment specialist immediately if

large quantities have been ingested or inhaled.

Specific Treatment No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media Recommended: alcohol-resistant foam, CO₂, powders, spray.

Unsuitable extinguishing media Do not use water jet

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self- contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and material for containment and cleaning up Small spill:

Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows.

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

6.4 Reference to other sections

See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

EN 469 will provide a basic level of protection for chemical incidents.

Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows.

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

Contaminated absorbent material may pose the same hazard as the spilt product. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits.

In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.

Mixture may charge electrostatically: always use earthing leads when transferring from one container to another.

Operators should wear antistatic footwear and clothing and floors should be of the conducting type.

Keep away from heat, sparks and flame. No sparking tools should be used.

Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.

Put on appropriate personal protective equipment (see Section 8).

Never use pressure to empty. Container is not a pressure vessel.

Always keep in containers made from the same material as the original one.

Comply with the health and safety at work laws.

Do not allow to enter drains or watercourses.

Information on fire and explosion protection

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

7.2 Conditions for safe storage, including any incompatibilities Store

in accordance with local regulations.

Notes on joint storage

Keep away from: oxidising agents, strong alkalis, strong acids.

Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight.

Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

7.3 Specific end use(s)

Recommendations: Not available. Industrial sector specific: Not available.

Solutions:

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Occupational exposure limits: No exposure limit value known

Recommended monitoring procedures:

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Derived no effect levels No

DNELs available.

Predicted no effect concentrations No

PNECs available.

8.2 Exposure controls Appropriate engineering controls

If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Individual protection measures

Hygiene measures:

Wash hands, forearms and face thoroughly after handling chemical products,

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection: before eating, smoking and using the lavatory and at the end of the working period.

Safety eyewear complying to EN 166 should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with sideshields.

Skin protection

Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

Wear suitable gloves tested to EN374.

Recommended, gloves(breakthrough time) > 8 hours: nitrile rubber.

For right choice of glove materials, with focus on chemical resistance and time of penetration, seek advice by the supplier of chemical resistant gloves.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Body protection:

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection:

If workers are exposed to concentrations above the exposure limit, they must use a respirator according to EN 140. Use respiratory mask with charcoal and dust filter when spraying this product, according to EN 14387(as filter combination A2-P2). In confined spaces, use compressed-air or fresh-air respiratory equipment. When use of roller or brush, consider use of charcoal filter.

Environmental exposure controls:

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties Appearance

Physical state Liquid.

Colour Not available. Odour Not available.

Odour threshold

pH

Not applicable

Not applicable

Not applicable Initial

boiling point and >90°- 320°C boiling range

Flash point Closed cup: 47°C – 62°C Evaporation rate Not available.

Flammability (solid, gas)

Burning time

Burning rate

Upper/lower flammability or

Not applicable.

Not applicable.

1.4 - 7.6% explosive

limits

Vapour pressure
Not available. Vapour density
Not available. Relative density

Solubility(ies)

Partition coefficient: n-octanol/

Not available.

Not available.
Not available.

Auto-ignition temperature Lowest known value: 280 to 470°C (536 to 878°F)

(hydrocarbons,

C10-C13, nalkanes, isoalkanes, cyclics, aromatics (225%),

(<0.1% Benzene).

Decomposition temperature: Not available. **Viscosity:**

Not available. Explosive properties: Not

available.

Oxidising properties: Not available.

9.2 Other information No

additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity: No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability: The product is stable.

10.3 Possibility of hazardous reactions Under normal conditions of storage and use, hazardous

reactions will not occur.

10.4 Conditions to avoid No specific data.

10.5 Incompatible materials Keep away from the following materials to prevent strong

exothermic reactions: oxidising agents, strong alkalis,

strong acids.

10.6 Hazardous decomposition products Under normal conditions of storage and use, hazardous

decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Acute toxicity estimates Not

available.

Specific target organ toxicity (single exposure) Not available.

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%), (<0.1% Benzene)	Category 1	Not determined	Not determined

Aspiration hazard

Product/ingredient name	Result	
hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%), (<0.1% Benzene)	ASPIRATION HAZARD - Category 1	

Potential acute health effects

Eye contact: No known significant effects or critical hazards. Inhalation:
No known significant effects or critical hazards. Ingestion: No known
significant effects or critical hazards. Skin contact: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics Skin contact

No

specific data.

Ingestion No specific data. **Inhalation** No specific data. **Eye contact:** No specific data.

Potential chronic health effects

General: Causes damage to organs through prolonged or repeated exposure.

Carcinogenicity: No known significant effects or critical hazards. Mutagenicity: No

known significant effects or critical hazards. **Teratogenicity**: No known significant effects or critical hazards. **Developmental effects**: No known significant effects or critical hazards. **Fertility effects**: No known significant

effects or critical hazards

SECTION 12: Ecological information

12.1 Toxicity

Conclusion/Summary: Water polluting material. May be harmful to the environment if released in

large quantities. This material is harmful to aquatic life with long lasting

effects.

12.2 Persistence and degradability Conclusion/Summary: Not available. 12.3

Bio accumulative potential

Product/ingredient name	LogPow	BCF	Potential
hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%), (<0.1% Benzene)	-	10 to 2500	high

12.4 Mobility in soil

Soil/water partition Coefficient (Koc)

Not available.

Mobility Not available.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable. vPvB: Not applicable.

12.6 Other adverse effects No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Do not allow to enter drains or watercourses. Material and/or container must be disposed of as hazardous waste.

European waste catalogue

08 01 11* Waste paint and varnish containing organic solvents or other dangerous substances

SECTION 14: Transport information

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Remarks

ADR/RID/IATA/IMDG:

Not dangerous goods if the product temperature is lower than the flash point (see section 9.)

14.1 UN number: 1306

14.2 UN proper shipping Name Elevated temperature liquid, flammable, n.o.s.

(hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics,

aromatics (2-25%), (<0.1% Benzene)

14.3 Transport hazard class(es)

14.4 Packing group 111

14.5 Environmental hazards No

14.6 Special precautions for user Transport within user's premises: always transport in

closed containers that are upright and secure. Ensure

that persons transporting the product know what to do in the event of an accident or spillage. Additional information

ADR / RID: Tunnel restriction code: (D/E)

Hazard identification number: 30

IMDG Emergency schedules (EmS)

13

IMDG Emergency schedules (EmS)

F-E, S-D

14.7 Transport in bulk Not available.

According to Annex II of Marpol and the IBC Code

IMDG Code Segregation group Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures Not applicable.

Other EU regulations

and articles

Europe inventory: Not determined.

Black List Chemicals: Not listed

Industrial emissions (integrated pollution prevention and con-

trol) -

Air Not listed Industrial emissions Not listed

(integrated pollution prevention and control)

- Water

Chemical Weapons Not listed

Convention List Schedule

I Chemicals

Chemical Weapons Not listed

Convention List Schedule

II Chemicals

Chemical Weapons

Convention List Schedule III Not listed

Chemicals

15.2 Chemical safety assessment This product contains substances for which Chemical

Safety Assessments are still required.

SECTION 16: Other information

Abbreviations and acronyms

ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification	
	Calculation method Calculation method	

Full text of abbreviated H statements

H304 May be fatal if swallowed and enters airways. H372 Causes damage to organs through prolonged or repeated exposure. H412 Harmful to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

Aquatic Chronic 3, H412 LONG-TERM AQUATIC HAZARD - Category 3 Asp. Tox. 1, H304 ASPIRATION HAZARD - Category 1 EUH066 Repeated exposure may cause skin dryness or cracking. STOT RE 1, H372 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

This information relates only to the specific material designated and may not be valid for such materials used in combination with any other materials or in any process. Such information is, to best of the company's knowledge and belief, accurate and reliable as of the date indicated. How ever warranty guarantee or representation is made to its accuracy, reliability or completeness. It's is the user's responsibility to satisfy themself as to the suitability of such information for their particular use.

Date of issue: 23.06.2021